

**FABORY-SPEDEC SN - SELF-DRILLING HEXAGON HEAD SCREWS WITH COLLAR - STEEL ZINC PLATED**
**FABORY-SPEDEC SN - ZELFBORENDE ZESKANTKRAAGBOUTEN - STAAL ELEKTROLYTISCH VERZINKT**
**FABORY-SPEDEC SN - VIS AUTO-PERCEUSES A TETE HEXAGONALE A EMBASE CYLINDRIQUE - ACIER ELZN**
**FABORY-SPEDEC SN - TORNILLOS AUTOTALADRAR DE CABEZA HEX. CON COLLARIN - ACERO GALV. ELECTROLITICO**
**FABORY-SPEDEC SN - SECHSKANTBOHRSCHRAUBEN MIT BUND - STAHL VERZINKT**

	ISO :-	<b>GROUPCODE</b>  ZINC PL. ☒ <b>31235</b> ZINC PL. ☒☒ <b>31230</b>		<b>ST</b>  <b>St</b>
	DIN : 7504 K NEN :- ANSI :- BS :- NF :-			

<b>d</b>	<b>ST4,2</b>	<b>ST4,8</b>	<b>ST5,5</b>	<b>ST6,3</b>
P	1,4	1,6	1,8	1,8
d <sub>c</sub>	8,8	10,5	11	13,2
k (max.)	4,25	4,45	5,45	6,45
s	7	8	8	10
L <sub>1</sub> ≈ ①	7	8	10	11

**SMALL PACKING DIMENSION CODE**

<b>d x L</b>	ZINC PL. <b>31235</b> ☒	<b>J09</b>	<b>d x L</b>	ZINC PL. <b>31235</b> ☒	<b>J09</b>	<b>d x L</b>	ZINC PL. <b>31235</b> ☒	<b>J09</b>
ST4,2 x 13MM	042.013	200	ST4,8 x 22MM	048.022	200	ST5,5 x 32MM	055.032	100
ST4,2 x 16MM	042.016	200	ST4,8 x 25MM	048.025	200	ST6,3 x 19MM	063.019	200
ST4,2 x 19MM	042.019	200	ST4,8 x 32MM	048.032	200	ST6,3 x 22MM	063.022	200
ST4,2 x 25MM	042.025	200	ST4,8 x 38MM	048.038	200	ST6,3 x 25MM	063.025	200
ST4,2 x 32MM	042.032	200	ST4,8 x 45MM	048.045	200	ST6,3 x 32MM	063.032	100
ST4,8 x 13MM	048.013	200	ST5,5 x 19MM	055.019	200	ST6,3 x 38MM	063.038	100
ST4,8 x 16MM	048.016	200	ST5,5 x 22MM	055.022	200	ST6,3 x 45MM	063.045	100
ST4,8 x 19MM	048.019	200	ST5,5 x 25MM	055.025	200	ST6,3 x 50MM	063.050	100

**LARGE PACKING DIMENSION CODE**

<b>d x L</b>	ZINC PL. <b>31230</b> ☒☒	<b>J09</b>	<b>d x L</b>	ZINC PL. <b>31230</b> ☒☒	<b>J09</b>	<b>d x L</b>	ZINC PL. <b>31230</b> ☒☒	<b>J09</b>
ST4,2 x 13MM	042.013	1000	ST4,8 x 25MM	048.025	1000	ST5,5 x 38MM	055.038	500
ST4,2 x 16MM	042.016	1000	ST4,8 x 32MM	048.032	1000	ST6,3 x 19MM	063.019	500
ST4,2 x 19MM	042.019	1000	ST4,8 x 38MM	048.038	500	ST6,3 x 22MM	063.022	500
ST4,2 x 25MM	042.025	1000	ST4,8 x 45MM	048.045	500	ST6,3 x 25MM	063.025	500
ST4,2 x 32MM	042.032	1000	ST4,8 x 50MM	048.050	500	ST6,3 x 32MM	063.032	500
ST4,8 x 13MM	048.013	1000	ST5,5 x 19MM	055.019	1000	ST6,3 x 38MM	063.038	500
ST4,8 x 16MM	048.016	1000	ST5,5 x 22MM	055.022	1000	ST6,3 x 45MM	063.045	500
ST4,8 x 19MM	048.019	1000	ST5,5 x 25MM	055.025	500	ST6,3 x 50MM	063.050	500
ST4,8 x 22MM	048.022	1000	ST5,5 x 32MM	055.032	500			

① Max. grip length KL = L - L<sub>1</sub>.  
 For guide values for FABORY-SPEDEC self-drilling screws type SN, see INFO page.