

**FABORY-SPEDEC SN - SELF-DRILLING CROSS RECESSED PAN HEAD SCREWS - STEEL ZINC PLATED**

FABORY-SPEDEC SN - ZELFBORENDE PANCILINDERSCHROEVEN MET KRUISGLEUF - STAAL ELVZ

FABORY-SPEDEC SN - VIS AUTO-PERCEUSES A TETE CYLYDRIQUE A EMPREINTE CRUCIFORME - ACIER ELZN

FABORY-SPEDEC SN - TORN. AUTOTALADRAR CON CABEZA CIL. ABOMB. CON HUECO CRUCIF. - ACERO GALV. ELECTR.

FABORY-SPEDEC SN - LINSEN-BOHRSCHRAUBEN MIT KREUZSCHLITZ - STAHL VERZINKT

	ISO :- <b>DIN : 7504 M-H</b> NEN :- ANSI :- BS :- NF :-	<b>GROUPCODE</b>  ZINC PL. ☒ <b>31255</b> ZINC PL. ☒☒ <b>31250</b>	<p>Ordering example: 31255 ST3,5 x 9,5</p>	<b>ST</b> <b>St</b>




<b>d</b>	<b>ST2,9</b>	<b>ST3,5</b>	<b>ST3,9</b>	<b>ST4,2</b>	<b>ST4,8</b>
P	1,1	1,3	1,3	1,4	1,6
dk	5,6	6,9	7,5	8,2	9,5
k	2,2	2,6	2,8	3,05	3,55
L1 ≈ ①	4,5	5	6	7	8
Nr. Phillips (H)	1	2	2	2	2

**SMALL PACKING**
**DIMENSION CODE**

<b>d x L</b>	<b>ZINC PL. 31255</b>	☒	<b>d x L</b>	<b>ZINC PL. 31255</b>	☒	<b>d x L</b>	<b>ZINC PL. 31255</b>	☒
	<b>J09</b>			<b>J09</b>			<b>J09</b>	
ST3,5 x 9,5MM	035.009	200	ST3,9 x 16MM	039.016	200	ST4,2 x 25MM	042.025	200
ST3,5 x 13MM	035.013	200	ST3,9 x 19MM	039.019	200	ST4,2 x 32MM	042.032	200
ST3,5 x 16MM	035.016	200						
ST3,5 x 19MM	035.019	200	ST4,2 x 13MM	042.013	200	ST4,8 x 13MM	048.013	200
ST3,5 x 25MM	035.025	200	ST4,2 x 16MM	042.016	200	ST4,8 x 16MM	048.016	200
			ST4,2 x 19MM	042.019	200	ST4,8 x 19MM	048.019	200

**LARGE PACKING**
**DIMENSION CODE**

<b>d x L</b>	<b>ZINC PL. 31250</b>	☒☒	<b>d x L</b>	<b>ZINC PL. 31250</b>	☒☒	<b>d x L</b>	<b>ZINC PL. 31250</b>	☒☒
	<b>J09</b>			<b>J09</b>			<b>J09</b>	
ST2,9 x 9,5MM	029.009	1000	ST3,9 x 19MM	039.019	1000	ST4,2 x 32MM	042.032	1000
			ST3,9 x 25MM	039.025	1000			
ST3,5 x 9,5MM	035.009	1000	ST3,9 x 32MM	039.032	1000	ST4,8 x 13MM	048.013	1000
ST3,5 x 13MM	035.013	1000				ST4,8 x 16MM	048.016	1000
ST3,5 x 16MM	035.016	1000	ST4,2 x 13MM	042.013	1000	ST4,8 x 19MM	048.019	1000
ST3,5 x 19MM	035.019	1000	ST4,2 x 16MM	042.016	1000	ST4,8 x 22MM	048.022	1000
ST3,5 x 25MM	035.025	1000	ST4,2 x 19MM	042.019	1000	ST4,8 x 25MM	048.025	1000
			ST4,2 x 22MM	042.022	1000	ST4,8 x 32MM	048.032	1000
ST3,9 x 13MM	039.013	1000	ST4,2 x 25MM	042.025	1000	ST4,8 x 38MM	048.038	500
ST3,9 x 16MM	039.016	1000				ST4,8 x 50MM	048.050	500

**ASSEMBLY SEQUENCE**


① Max. grip length KL = L - L1.

For guide values for FABORY-SPEDEC self-drilling screws type SN, see INFO page.

**WARNING:** electro-galvanizing of these products may cause hydrogen embrittlement.