


PARALLEL PINS WITH INTERNAL THREAD - HARDENED - STEEL

CILINDRISCHE PENNEN MET BINNENDRAAD - GEHARD - STAAL

GOUPILLES CYLINDRIQUES A TROU TARAUDE - TREMPÉES - ACIER

PASADORES CILINDRICOS ROSCA INTERIOR - TEMPLADO - ACERO

ZYLINDERSTIFTE MIT INNENGEWINDE - GEHÄRTET - STAHL



ISO : 8735 A
DIN : 7979 D
NEN : 2464
ANSI : -
BS : -
NF : -

GROUPCODE

STEEL

39090



Ordering example:
39090 6 x 16

St^①

d (m6)	6	8	10	12	16	20
d1	M4	M5	M6	M6	M8	M10
t1	6	8	10	10	12	16

DIMENSION CODE

d x L1 ^②	STEEL 39090 L11	⊗	d x L1 ^②	STEEL 39090 L11	⊗	d x L1 ^②	STEEL 39090 L11	⊗
6 x 16MM	060.016	50	8 x 70MM	080.070	10	12 x 60MM	120.060	10
6 x 20MM	060.020	50				12 x 70MM	120.070	10
6 x 24MM	060.024	50	10 x 20MM	100.020	25	12 x 80MM	120.080	5
6 x 28MM	060.028	50	10 x 24MM	100.024	25	12 x 100MM	120.100	5
6 x 30MM	060.030	50	10 x 28MM	100.028	25			
6 x 32MM	060.032	25	10 x 30MM	100.030	25	16 x 32MM	160.032	5
6 x 40MM	060.040	25	10 x 32MM	100.032	25	16 x 40MM	160.040	5
6 x 50MM	060.050	25	10 x 36MM	100.036	10	16 x 50MM	160.050	5
6 x 60MM	060.060	25	10 x 40MM	100.040	10	16 x 60MM	160.060	5
			10 x 45MM	100.045	10	16 x 70MM	160.070	5
8 x 16MM	080.016	50	10 x 50MM	100.050	10	16 x 80MM	160.080	5
8 x 20MM	080.020	50	10 x 60MM	100.060	10	16 x 100MM	160.100	5
8 x 24MM	080.024	25	10 x 70MM	100.070	10	16 x 120MM	160.120	5
8 x 28MM	080.028	25	10 x 80MM	100.080	10			
8 x 30MM	080.030	25				20 x 50MM	200.050	5
8 x 32MM	080.032	25	12 x 24MM	120.024	10	20 x 60MM	200.060	5
8 x 36MM	080.036	25	12 x 28MM	120.028	10	20 x 70MM	200.070	5
8 x 40MM	080.040	25	12 x 32MM	120.032	10	20 x 80MM	200.080	5
8 x 45MM	080.045	25	12 x 36MM	120.036	10	20 x 100MM	200.100	5
8 x 50MM	080.050	10	12 x 40MM	120.040	10	20 x 120MM	200.120	5
8 x 60MM	080.060	10	12 x 50MM	120.050	10			

① Steel, hardness 60 ± 2 HRC.

② The nominal length L1 is **inclusive** the rounded ends with tolerance js15.
For tolerance fields, see section 15.